

# REIKU-Kabelschutz-Wellrohre

## REIKU Tubings for Cable Protection

	<table border="0"> <tr> <td><b>PU</b> Polyurethan, thermopl.</td> <td>polyurethane, thermopl.</td> </tr> <tr> <td><b>BIO</b> BIO, PA 11</td> <td>BIO, PA 11</td> </tr> <tr> <td><b>R</b> Wellrohr</td> <td>corrugated tubing</td> </tr> <tr> <td><b>R</b> Roboterversion</td> <td>robot version</td> </tr> <tr> <td><b>V</b> verstärkte Version</td> <td>strengthened version</td> </tr> <tr> <td><b>B</b> schwarz</td> <td>black</td> </tr> <tr> <td><b>10</b> Nennweite</td> <td>nominal width</td> </tr> <tr> <td><b>F</b> Feinprofil</td> <td>fine profile</td> </tr> <tr> <td><b>G</b> Grobprofil</td> <td>broad profile</td> </tr> <tr> <td><b>M</b> Mittelprofil</td> <td>middle profile</td> </tr> <tr> <td><b>L</b> Wellrohr Längsschlitz</td> <td>conduit longitudinal slit</td> </tr> </table>	<b>PU</b> Polyurethan, thermopl.	polyurethane, thermopl.	<b>BIO</b> BIO, PA 11	BIO, PA 11	<b>R</b> Wellrohr	corrugated tubing	<b>R</b> Roboterversion	robot version	<b>V</b> verstärkte Version	strengthened version	<b>B</b> schwarz	black	<b>10</b> Nennweite	nominal width	<b>F</b> Feinprofil	fine profile	<b>G</b> Grobprofil	broad profile	<b>M</b> Mittelprofil	middle profile	<b>L</b> Wellrohr Längsschlitz	conduit longitudinal slit	
<b>PU</b> Polyurethan, thermopl.	polyurethane, thermopl.																							
<b>BIO</b> BIO, PA 11	BIO, PA 11																							
<b>R</b> Wellrohr	corrugated tubing																							
<b>R</b> Roboterversion	robot version																							
<b>V</b> verstärkte Version	strengthened version																							
<b>B</b> schwarz	black																							
<b>10</b> Nennweite	nominal width																							
<b>F</b> Feinprofil	fine profile																							
<b>G</b> Grobprofil	broad profile																							
<b>M</b> Mittelprofil	middle profile																							
<b>L</b> Wellrohr Längsschlitz	conduit longitudinal slit																							

### PU R R B Polyurethan, thermopl., für Roboter, schwarz polyurethane, thermopl., for robots, black 105°C

Bestell-Nr. Article no. schwarz black	NW mm	M/PG	d2	d1	Radius mm (stat.) (dyn.)		kg/100 m	(VE) m (PU) m
PU R R B-07G	07	10/07	10,0	6,3	15	40	2,5	100
PU R R B-10F	10	12/09	13,0	9,3	20	50	3,7	100
PU R R B-12F	12	16/11	15,7	11,6	25	65	4,5	50
PU R R B-17G	17	25/16	21,6	15,3	30	80	9,0	50
PU R R B-23G	23	32/21	28,4	21,4	40	100	14,2	50
PU R R B-29G	29	40/29	34,1	27,7	50	120	17,0	50
PU R R B-36F	36	50/36	42,6	35,6	55	170	25,5	30
PU R R B-36G	36	50/36	43,2	35,3	60	180	23,5	30
PU R R B-42M	42	50/42	50,0	41,0	60	190	30,0	30
PU R R B-48F	48	63/48	54,5	48,0	60	200	32,0	30
PU R R B-48G	48	63/48	55,0	46,5	70	200	32,0	30
PU R R B-52G	52		62,4	52,4	150	300	44,0	10/30
PU R R B-68G	68		79,2	66,2	170	350	58,0	10/30
PU R R B-70G	70		83,4	69,5	150	350	73,0	10/30
PU R R B-95G	90		106,4	89,0	180	410	101,0	10/30

UL recognized File E 168970 (M) 105°C für Nennweite 52 und 70 for NW 52 and NW 70

### PU R V B Polyurethan, thermopl., verstärkte Version, schwarz polyurethane, thermopl., strengthened version, black 105°C

Bestell-Nr. Article no. schwarz black	NW mm	M/PG	d2	d1	Radius mm (stat.) (dyn.)		kg/100 m	(VE) m (PU) m
PU R V B-48 F	48	63/48	54,5	47,0	100	250	35,0	30
PU R V B-52 G	52		62,2	52,0	150	300	47,0	10/30
PU R V B-70 G	70		82,6	68,6	170	400	91,0	10/30

UL recognized File E 168970 (M) 105°C für Nennweite 52 und 70 for NW 52 and NW 70

### BIO R R B BIO Polyamid 11, auf Rizinus-Öl-Basis, schwarz BIO polyamide 11, base of castor oil, black

Bestell-Nr. Article no. schwarz black	NW mm	M/PG	d2	d1	Radius mm (stat.) (dyn.)		kg/100 m	(VE) m (PU) m
BIO R R B-10F	10	12/09			20	50		100
BIO R R B-12F	12	16/11	15,7	11,9	25	65	3,5	50
BIO R R B-17F	17	25/16	21,2	16,5	30	80	5,5	50
BIO R R B-23F	23	32/21	28,5	22,6	35	90	9,2	50
BIO R R B-29F	29	40/29	34,3	28,0	45	120	13,4	50
BIO R R B-36G	36	50/36	42,2	35,5	60	180	16,0	30
BIO R R B-48G	48	63/48	54,5	46,5	70	200	23,6	30
BIO R R B-52G	52		63,0	52,0	125	300	36,5	10/30
BIO R R B-70G	70		82,5	70,0	150	350	51,0	10/30

Mit Längsschlitz auf Anfrage longitudinal slit on request